


SPACER SUPPORT


- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: NATURAL/BLACK
- ◆ UNIT: mm



P.C.B Ø4.0
THICKNESS 1.2-1.7



P.C.B Ø4.0
THICKNESS 1.2-1.9



FOR TCBS-38.5

FOR M3 SELF TAPPED SCREW

PART NO	A	PACKAGE
TCBS-5	5.0	1000
TCBS-6A	6.0	
TCBS-6	6.35	
TCBS-7	7.0	
TCBS-9.5	9.5	
TCBS-10	10.0	
TCBS-12.5	12.5	
TCBS-15	15.0	
TCBS-20	20.0	
TCBS-24.5	24.5	
TCBS-25	25.0	
TCBS-26	26.0	
TCBS-30	30.0	
TCBS-35	35.0	
TCBS-38.5	38.5	


1

SPACER SUPPORT

- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: NATURAL/BLACK
- ◆ UNIT: mm



P.C.B Ø4.0
THICKNESS 1.2-1.7



FOR M3 SELF TAPPED SCREW



PART NO	PACKAGE
TCBS-18	1000

SPACER SUPPORT



- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: NATURAL/WHITE/BLACK
- ◆ UNIT: mm



THICKNESS 1.2-1.7



THICKNESS 1.2-1.7



FOR SCREW: S

PART NO	PACKAGE
TCBT-3.6	1000

PART NO	7.0	7.7	8.5	16.0	6.9	5.9	6.9	2.4	2.6	2.6	2.4	4-40 UNC	4-40 UNC	1000
TCBT-7	7.0	7.7	8.5	16.0	6.9	5.9	6.9	2.4	2.6	2.6	2.4	4-40 UNC	4-40 UNC	1000
TCBT-7.7	7.7	7.7	8.5	16.0	6.9	5.9	6.9	2.4	2.6	2.6	2.4	M3	4-40 UNC	
TCBT-8.5	8.5	7.7	8.5	16.0	6.9	5.9	6.9	2.4	2.6	2.6	2.4	M3	4-40 UNC	
TCBT-16	16.0	7.7	8.5	16.0	6.9	5.9	6.9	2.4	2.6	2.6	2.4	4-40 UNC	4-40 UNC	

