


IC Carrier-Pin Socket Header

TOPTEK®


HARDWARE ELECTRONIC MANUFACTURER



www.toptek-co.com

TOPTEK srl
10015 - IVREA (TO) - ITALY
tel. +39 0125 251 211 - fax +39 0341 367 607
info@toptek-co.com


Pitch 1.27 mm



SPLCC - XX - U

XX: No. of Contacts (20, 28, 32, 44, 52, 68, 84)
U: RoHS + PPS

Pitch 2.54 mm




DPLCC - XX - L/U

1 2

1. No. of Contacts (20, 28, 32, 44, 52, 68, 84)
2. RoHS + PBT/PPS

Pitch 1.778 mm



IC2 - 3/4/6/7 XX - L

1 2 3

1.3: 0.07x0.3/4: 0.07x0.4/6: 0.07x0.6/7: 0.07x0.75
2. No. of Contacts (3: 16, 20, 22, 24/4: 24, 28, 30, 32/6: 40, 42, 48, 52, 54, 56, 58, 60, 62, 64/7: 64)
3. RoHS + PBT

Pitch 2.54 mm




IC1 - 3/6 XX - L

1 2 3

1.3: 0.1x0.3/6: 0.1x0.6
2. No. of Contacts (3: 6, 8, 10, 14, 16, 18, 20, 22, 24, 28/6: 24, 28, 32, 36, 40, 42, 48, 50, 52)
3. RoHS + PBT

Pitch 1.0 mm



EC5M - XX - U

1 2 3

1. R: Right Angle, S: Straight, M: SMT
2. No. of Contacts (04~120)
3. RoHS + PBT

Pitch 1.27 mm




EC3M - XX - U

1 2 3

1. M: SMT
2. No. of Contacts (04~36)
3. RoHS + PPS

Pitch 2.54 mm




EC1S - XX - L

1 2 3

1. R: Right Angle, S: Straight, M: SMT
2. No. of Contacts (04~120)
3. RoHS + PBT

Pitch 2.54 mm



EC1R - XX - L

1 2 3

1. R: Right Angle, S: Straight, M: SMT
2. No. of Contacts (04~108)
3. RoHS + PBT

Pitch 1.0 mm




PCI5 - S - 1 - XX - U

1 2 3

1. S: Straight
2. No. of Contacts (36)
3. RoHS + PPS

Pitch 1.0 mm




PCI5 - S - 1 - XX - U

1 2 3

1. S: Straight
2. No. of Contacts (64)
3. RoHS + PPS

Pitch 1.0 mm



PCI5 - S - 1 - XX - U

1 2 3

1. S: Straight
2. No. of Contacts (98)
3. RoHS + PPS

Mini PCI express
Pitch 0.5 mm



MPCI - A05 XX - U

1 2 3

1. M: SMT
2. No. of Contacts (52)
3. RoHS + PPS

CONNECTORS MANUFACTURER

TOPTEK®
HARDWARE ELECTRONIC MANUFACTURER

www.toptek-co.com

11

*


2

I C Carrier - Machine Pin Header

Pb

RoHS


Pitch 1.27 mm
SMT STR



MH3M - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No.of Contacts (02 ~ 50)
2.RoHS + PPS


Pitch 1.27 mm
SMT R/A



MH3H - 1 - $\frac{XX}{1}$ - $\frac{U}{2}$

1.No.of Contacts (02 ~ 50)
2.RoHS + PPS


Pitch 1.27 mm
RA



MH3R - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No.of Contacts (02 ~ 50)
2.RoHS + PPS


Pitch 1.27 mm
STR



MH3S - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No.of Contacts (02 ~ 50)
2.RoHS + PPS


Pitch 1.778 mm
STR



MH7S - 1 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No.of Contacts (02 ~ 32)
2.RoHS + PPS


Pitch 2.0 mm
SMT R/A



MH2H - 1 - $\frac{XX}{1}$ - $\frac{U}{2}$

1.No.of Contacts (02 ~ 40)
2.RoHS + PPS


Pitch 2.0 mm
SMT STR



MH2M - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.0 mm
RA



MH2R - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.0 mm
STR



MH2S - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.54 mm
SMT STR



MH1M - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.54 mm
SMT STR



MH1M - 1/2 $\frac{XX}{1}$ - 1/2 - $\frac{U}{2}$

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.54 mm
RA



MH1R - 1/2 $\frac{XX}{1}$ - $\frac{U}{2}$

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.54 mm
STR



MH1S - 1/2 XX - XXX - U
1 2

1.No. of Contacts(01~40)
2.RoHS + PPS


Pitch 1.27mm H=4.1mm.
SMT



MS3M - 1/2 XX - U
1 2

1.No. of Contacts(02~50)
2.RoHS + PPS


Pitch 1.27mm H=4.1mm.
RA



MS3R - 1/2 XX - U
1 2

1.No. of Contacts(02~50)
2.RoHS + PPS

Pitch 1.27mm H=4.1mm.
STR



MS3S - 1/2 XX - U
1 2

1.No. of Contacts(02~50)
2.RoHS + PPS


Pitch 1.778mm H=3.0mm
STR



MS7S - 1 XX - XXX - U
1 2

1.No. of Contacts(02~32)
2.RoHS + PPS


Pitch 2.0mm H=2.8mm
SMT



MS2M - 1/2 XX - U
1

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.0mm H=2.8mm
RA



MS2R - 1/2 XX - U
1 2

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.0mm H=2.8mm
STR



MS2S - 1/2 XX - XXX - U
1 2

1.No. of Contacts(02~40)
2.RoHS + PPS


Pitch 2.54mm
SMT



MS1M30 - 1/2 XX - U
1 2 3

1.H=3.0mm
2.No. of Contacts(02~40)
3.RoHS + PPS


Pitch 2.54mm
SMT



MS1MA30 - 1/2 XX - 1/2 - U
1 2 3

1.H=3.0mm
2.No. of Contacts(02~40)
3.RoHS + PPS


Pitch 2.54mm
SMT



MS1M70 - 1/2 XX - U
1 2 3

1.H=7.0mm
2.No. of Contacts(02~40)
3.RoHS + PPS

Pitch 2.54mm
RA



MS1R30 - 1/2 XX - U
1 2 3

1.H=3.0mm
2.No. of Contacts(02~40)
3.RoHS + PPS

CONNECTORS MANUFACTURER

TOPTEK®
HARDWARE ELECTRONIC MANUFACTURER

www.toptek-co.com


11
*
4

I C Carrier - Pin / Socket Header

Pb

RoHS


Pitch 2.54mm
RA



MS1R42 - 1/2 XX - U
1 2 3

1.H=4.2mm
2.No. of Contacts(02~40)
3.RoHS + PPS


Pitch 2.54mm
RA



MS1R70 - 1/2 XX - U
1 2 3

1.H=7.0mm
2.No. of Contacts(02~40)
3.RoHS + PPS

Pitch 2.54mm H=3.0mm
STR



MS1S - 1/2 XX - XXX - U
1 2

1.No. of Contacts(01~40)
2.RoHS + PPS


Pitch 2.54mm H=3.0mm
STR



MS1SQ - 1/2 XX - XXX - U
1 2

1.No. of Contacts(01~40)
2.RoHS + PPS


Pitch 2.54mm
STR



MS1SXX - 1/2 XX - XXX - U
1 2 3

1.H=4.2/7.0mm
2.No. of Contacts(01~40)
3.RoHS + PPS


Pitch 2.54mm 482.H=1.9mm
540.H=3.0mm
STR



MS1S - 1/2 XX - 540 - U
1 2

1.No. of Contacts(01~40)
2.RoHS + PPS


Pitch 1.778mm



MHIC7 - 4/6/7 XX - L
1 2 3

1.4:0.07x0.4/6:0.07x0.6/7:0.07x0.75
2.No. of Contacts(4:24,28,30,32,48/6:20,24,28,40,42,48,52,56,64,68/7:64)
3.RoHS + PBT


Pitch 1.778mm



MSIC7 - 4/6/7 XX - L
1 2 3

1.4:0.07x0.4/6:0.07x0.6/7:0.07x0.75
2.No. of Contacts(4:24,28,30,32,48/6:20,24,28,40,42,48,52,56,64,68/7:64)
3.RoHS + PBT


Pitch 2.54mm



MHIC - 3/4/6/9 XX - L
1 2 3

1.3:0.1x0.3/4:0.1x0.4/6:0.1x0.6/9:0.1x0.9
2.No. of Contacts(3:6,8,10,14,16,18,20,22,24,28/4:20,22,24,28,32,48/6:24,28,32,36,40,42,48,50,52/9:50,52,64)
3.RoHS + PBT


Pitch 2.54mm



MHICM - 3/4/6 XX - U
1 2 3

1.3:0.1x0.3/4:0.1x0.4/6:0.1x0.6
2.No. of Contacts(3:6,8,10,14,16,18,20,22,24,28/4:20,22,24,28,32,48/6:24,28,32,36,40,42,48,50,52)
3.RoHS + PPS


Pitch 2.54mm



MSICM - 3/4/6 XX - U
1 2 3

1.3:0.1x0.3/4:0.1x0.4/6:0.1x0.6
2.No. of Contacts(3:6,8,10,14,16,18,20,22,24,28/4:20,22,24,28,32,48/6:24,28,32,36,40,42,48,50,52)
2.RoHS + PPS

Pitch 2.54mm



MSICR - 3/6 XX - 1/2 - U
1 2 3

1.3:0.1x0.3/6:0.1x0.6
2.No. of Contacts(3:6,8,10,14,16,18,20,22,24,28/6:24,28,32,36,40,42,48,50,52)
3.RoHS + PPS