

# Ø 16 mm

# **TOPTEK®**

## C-TOP-16HJ-L






Diameter: Ø 16mm Switch Rating: 3A/250VAC Contact Configuration: 1NO Operation Type: Maintained The Front Shape: High The Crust Material:

Stainless steel

IP Degree: IP67, IK10



#### C-TOP-16F-10EM




Diameter: Ø 16mm Color: R, G, Y, O, B, W Switch Rating: 3A/250VAC Contact Configuration: 1NO Operation Type: Momentary The Front Shape: Flat Lamp type: Ring illuminated (LED) The Crust Material:

Stainless steel

Copper plating

IP Degree: IP67, IK10



## C-TOP-16H-10EM




Diameter: Ø 16mm Switch Rating: 3A/250VAC Contact Configuration: 1NO Operation Type: Momentary The Front Shape: High Lamp type: Ring illuminated (LED) The Crust Material:

Stainless steel

Copper plating

IP Degree: IP67, IK10



#### C-TOP-16F-10EPM




Diameter: Ø 16mm Switch Rating: 3A/250VAC Contact Configuration: 1NO Operation Type: Momentary The Front Shape: Flat Lamp type: Power symbol illuminated (LED) The Crust Material:

Stainless steel

Copper plating

IP Degree: IP67, IK10



www.toptek-co.com

info@toptek-co.com