Ø 19 mm

CA-TOP-19F-EP



Diameter: Ø 19mm Color: R, G, Y, O, B, W Switch Rating: 5A/250VAC

Contact Configuration: 1NO 1NC/ 0218 **2NO 2NC**

Operation Type: Momentary

IP Degree: IP67, IK10

Maintained(Z) The Front Shape: Flat Lamp type: Power symbol illuminated(LED) The Crust Material: Stainless steel

CA-TOP-19-K



Diameter: Ø 19mm Color: R, G, Y, O, B, W Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC/

2NO 2NC Operation Type:


> 2 Position 3 Position

The Front Shape: Selector

Light way: Arrow

The Crust Material: Stainless steel

IP Degree: IP67, IK10



CA-TOP-19B-SR




Diameter: Ø 19mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC/ 2NO

Operation Type: Push-Lock Turn-reset

The Front Shape: Ball Light way: Arrow

The Crust Material: Stainless steel

IP Degree: IP65, IK10



CA-TOP-19A-SR



Diameter: Ø 19mm Switch Rating: 5A/250VAC

Contact Configuration: 1NO 1NC/ 2NO

Operation Type: Push-Lock Turn-reset

The Front Shape: Ball Light way: Arrow

The Crust Material: Stainless steel

IP Degree: IP65, IK10

