# Ø 22 mm


## I-TOP-22-11E



Diameter: Ø 22mm Color: R, G, Y, O, B, W Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC Operation Type:

Momentary

Maintained(Z)
 The Front Shape: Flat
 Lamp type: Ring illuminated (LED)
 The Crust Material: Stainless steel
 IP Degree: IP67, IK10



#### I-TOP-22-11D




Diameter: Ø 22mm
Color: R, G, Y, O, B, W
Switch Rating: 5A/250VAC
Contact Configuration: 1NO 1NCE
Operation Type:

Momentary

Maintained(Z)

The Front Shape: Flat Lamp type: Dot illuminated (LED) The Crust Material: Stainless steel

IP Degree: IP67, IK10



#### I-TOP-22-11EP



Diameter: Ø 22mm
Color: R, G, Y, O, B, W
Switch Rating: 5A/250VAC
Contact Configuration: 1NO 1NC
Operation Type:


Momentary

Maintained(Z)

The Front Shape: Flat Lamp type: Power symbol illuminated (LED)

The Crust Material: Stainless steel

IP Degree: IP67, IK10



### I-TOP-S1-22F



Diameter: Ø 22mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:


Momentary

Maintained(Z)

Front Change Flat

The Front Shape: Flat The Crust Material: Stainless steel

IP Degree: IP67, IK10



14 \* 56

A nti-vandal Switch