

## Ø 22 mm

# **TOPTEK®**

#### I-TOP-S1-22B






Diameter: Ø 22mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary

Maintained(Z) The Front Shape: Ball

The Crust Material: Stainless steel

IP Degree: IP67, IK10



#### I-TOP-S1-22H



Diameter: Ø 22mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary

Maintained(Z)

The Front Shape: High

The Crust Material: Stainless steel

IP Degree: IP67, IK10

### I-TOP-S1-22F-L



Diameter: Ø 22mm Color: R, G, Y, O, B, W Switch Rating: 5A/250VAC **Contact Configuration:** 1NO 1NC /2NO 2NC Operation Type:

Momentary

Maintained(Z)

The Front Shape: Flat

Lamp type: Dot illuminated (LED) The Crust Material: Stainless steel

IP Degree: IP67, IK10

#### I-TOP-S1-22F-D



Diameter: Ø 22mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary Maintained(Z)

The Front Shape: Flat

Lamp type: Dot illuminated (LED) The Crust Material: Stainless steel

IP Degree: IP67, IK10

