

Ø 28 mm

TOPTEK®

S-TOP-28B






Diameter: Ø 28mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary

Maintained(Z)

The Front Shape: Ball The Crust Material: Stainless st

IP Degree: IP67, IK10



S-TOP-28H




Diameter: Ø 28mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary

Maintained(Z)

The Front Shape: Flat The Crust Material: Stainless steel

IP Degree: IP67, IK10



S-TOP-28F-E



Diameter: Ø 28mm Color: R, G, Y, O, B, W Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary


Maintained(Z)

Lamp type: Ring illuminated (LED)

The Front Shape: Flat

The Crust Material: Stainless steel

IP Degree: IP67, IK10



S-TOP-28F-D



Diameter: Ø 28mm Switch Rating: 5A/250VAC Contact Configuration: 1NO 1NC /2NO 2NC Operation Type:

Momentary

Maintained(Z)

Lamp type: Dot illuminated (LED)

The Front Shape: Flat

The Crust Material: Stainless steel

IP Degree: IP67, IK10

